

AGME RA RADIAL RIVETING MACHINES

MODEL	RA-4	RA-6	RA-12	RA-14	RA-16	RA-18	RA-20
Max. final diameter in 400 N/mm² steel	4 mm	6 mm	12 mm	14 mm	16 mm	18 mm	20 mm
Adjustable riveting stroke	5-30 mm	5-40 mm	5-40 mm	5-50 mm	5-50 mm	5-50 mm	5-50 mm
Max. air pressure	6 bars	6 bars	6 bars	6 bars	-	6 bars	-
Max. hydraulic force	-	-	-	-	40 bars	-	65 bars
Axial force	245 daN	475 daN	1.265 daN	1.880 daN	2.500 daN	3.240 daN	4.000 daN
Adjustable riveting time	0-5 sec.	0-5 sec.	0-5 sec	0-5 sec	0-5 sec	0-5 sec	0-5 sec
Power circuit (other please consult)	400V 50Hz	400V 50Hz	400V 50Hz	400V 50Hz	400V 50Hz	400V 50Hz	400V 50Hz
Power rating	0,3 kW	0,4 kW	0,7 kW	1,6 kW	2,8 kW	1,6 kW	2,8 kW
Control circuit	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC
Two hand safety control	Included	Included	Included	Included	Included	Included	Included
Operation control in 6 languages	Included	Included	Included	Included	Included	Included	Included
Parts counters	Included	Included	Included	Included	Included	Included	Included
Stroke centesimal adjustment	Included	Included	Included	Included	Included	Included	Included
Weight	155 Kg	155 Kg	160 Kg	285 KG	290 Kg	300 Kg	295 Kg

- The RA-4 and RA-30 riveting machines are built on customer's request

